

7845GSMR*

DIGITAL CELLULAR
COMMUNICATOR

*With Remote
Service Capability



Honeywell is focused on providing the future of alarm communication solutions for the security industry. Alternative communication methods are critical in the marketplace due to VoIP, migration from POTS and global growth of digital networks.

Honeywell's 7845GSMR delivers secure, reliable and complementary digital communications via the GSM (Global System for Mobile) network. Our use of Dual-Path GPRS service with SMS backup provides substantial benefits to protect your investment by future-proofing your recurring revenue.

This groundbreaking communications solution offers full data reporting and uploading/downloading with most Honeywell control panels. In addition, with on-board zone inputs and optional dialer capture capability we're compatible with other manufacturers' security panels as well.

All signals are delivered to Honeywell's AlarmNet Network Control Center, which routes the information to the appropriate central station. The state of the art AlarmNet Network Control Center is fully redundant and monitored 24/7. AlarmNet has the ability to route messages using AlarmNet-i and 800 PLUS services, providing true redundancy and multi-path message delivery.

FEATURES

- **Universal Control Panel Compatibility** – Flexible modes of operation allow ECP alarm reporting by Honeywell control panels, 4204 relay mode for Honeywell controls (that do not support ECP alarm reporting) and zone triggering for use with other control panels.
- **Dialer Capture Ready** – Compatible with Dialer Capture Intelligence Device DCID (for LYNX) or DCID-EXT (other control panels). Captures Contact ID messages from the panel's phone line and sends them to the central station via the GSM radio.
- **Six Input Zones** – Each zone can be configured for +V, -V, or EOLR triggering. Each zone can be programmed for inverted operation, delayed reporting and restoral reporting. Zone 1 can distinguish between pulsed and steady inputs.
- **Full Contact ID or ADEMCO High-Speed Reporting** – Contact ID reporting using ECP mode with compatible Honeywell control panels or combined with dialer capture for non-ECP capable control panels.
- **Tamper Protected Enclosure** – Built-in tamper sends a report when a tamper condition is detected and a restore when cleared.
- **Built-in Power Supply** – On board charging circuit design accommodates back-up battery. Includes primary power and battery supervision.
- **Back-Up Battery** – 6V 3.1Ah supplied to deliver up to 24 hours of standby operation.
- **256-bit AES Encryption** – Advanced encryption standard used for secure communications.
- **Dual-Path Technology** – Uses GPRS (General Packet Radio Service) as primary digital cellular path and automatically switches to SMS (Short Message Service) if GPRS is unavailable.
- **Upload/Download** – With select Honeywell control panels using GPRS. Requires Compass version 1.5.8.54a or higher.
- **Dynamic Signaling with Certain Honeywell Control Panels** – Provides management of control panel dialer and digital cellular communicator. Programmable priority and delays determine signal path.
- **Diagnostic LEDs** – Provide signal strength and status indications.
- **QOS** – Quality of Service diagnostics via AlarmNet supply vital information including when message was received, battery voltage, input voltage, signal strength and message path.
- **Web-Based Programming** – Allows complete interactive programming from AlarmNet Direct. <https://services.alarmnet.com/AlarmnetDirect>
- **Intelligent Supervision** – Any message generated serves as a supervision message per optional 24 hour or 30 day intervals. This feature effectively limits required messages to be sent.
- **Remote Services Capability*** – Optional Total Connect value-added web-based or SMS system control as well as e-mail notification of system events.

*Service subscription required.

7845GSMR

DIGITAL CELLULAR COMMUNICATOR

ACCESSORIES

7720P Programmer



K14139 Battery
(Included)



1332 Transformer
(1332CN for Canada)
(Included)



DCID
Dialer Capture Intelligence Device
(For Non-ECP LYNX controls)



DCID-EXT
Dialer Capture Intelligence Device
(For Non-ECP capable control panels)

SPECIFICATIONS

Power

- **Input Operating Voltages:**
10.5–14.3VDC or 9–16.5VAC
- **Backup Battery:**
6V 3.1A (24 hrs. standby)
- **Current Requirements:**
60mA standby – 400mA during transmission
- **Transmission Power:**
850MHz 1 Watt to 1900MHz
2 Watts

Mechanical

- **Dimensions:** 8" H x 7.5" W x 1.86" D
- **Operating Temperature:**
-22° to 140° F (-30° to 60° C)
- **Humidity:**
0% – 90% non-condensing

UL/ULC Listings

- UL 365 – Police Station Connected Burglar Alarm Units and Systems
- UL 1610 – Central Station Burglar Alarm Units
- UL 1635 – Digital Alarm Communicator System Units

- UL 985 – Household Fire Warning System Units
- CAN/ULC-S303-M91 (First Edition) – Local Burglar Alarm Units and Systems
- CAN/ULC-S304-M88 (First Edition) – Central and Monitoring Station Burglar Alarm Units
- CAN/ULC Subject C1023-1974 (First Edition) – Household Burglar Alarm System Units
- CAN/ULC-S545-02 (Second Edition) – Residential Fire Warning System Control Units

ORDERING

- 7845GSMR** Digital Cellular Communicator with Remote Services Capability
- 7845GSMRCN** Digital Cellular Communicator for Canada with Remote Services Capability
- 7845GSMRG** California Compliant Digital Cellular Communicator with Remote Services Capability

Honeywell Security & Custom Electronics

Honeywell
2 Corporate Center Drive
Melville, NY 11747
Tel: 800.467.5875
www.honeywell.com

Honeywell

L/7845GSMR/D
August 2007
© 2007 Honeywell International Inc.